

Gaszähler

- über Hall Sensor
- <https://www.laszloturi.eu/2023/12/how-to-integrate-mechanical-gas-meter.html>
- SS49E.PDF
- <https://arduinomodules.info/ky-024-linear-magnetic-hall-module/>
- <https://github.com/red5alex/hall-effect-gas-meter-sensor>

Aufbau

- Sensor : SS49E

Kalibrieren

ALT

[download](#)

```
substitutions:
  devicename: "iot-kl-wl-sc-gaszaehler"

esphome:
  name: iot-kl-wl-sc-gaszaehler
  friendly_name: IOT_KL_WL_SC_GasZaehler

rp2040:
  board: rpipicow

preferences:
  flash_write_interval: 5min # set to 5min to prevent wearing out the
  onboard flash module too quickly

# Enable logging
logger:
  baud_rate: 115200
  level: DEBUG

status_led:
  pin: 32

globals:
  - id: total_pulses          # Gesamte Impulse (Counter)
    type: int
    restore_value: true      # Speichert im Flash (nach Neustart)
```

```
erhalten)
  initial_value: '0'
  - id: impuls_factor          # Kalibrierung: m³ pro Impuls (z. B.
0.01)
  type: float
  restore_value: true
  initial_value: '0.01'      # Passe an deinen Zähler an!
  - id: initial_consumption  # Offset: Aktueller Zählerstand zum Start
  type: float
  restore_value: true
  initial_value: '1234.56'  # Dein aktueller Zählerstand (hier
kalibrieren!)

# Enable Home Assistant API
api:
  encryption:
    key: !secret api_encryption_key
  services:
    - service: set_initial_gas_reading
      variables:
        reading: float
      then:
        - lambda: |-
            id(initial_consumption) = reading;
            ESP_LOGI("calib", "Initialwert gesetzt: %.3f m³",
reading);
        - homeassistant.service:
            service: persistent_notification.create
            data:
              title: "Gaszähler kalibriert"
              message: "Neuer Startwert: {{ reading }} m³"

ota:
  - platform: esphome
    password: !secret ota_password

wifi:
  ssid: !secret wifi_ssid
  password: !secret wifi_password
  ap:
    ssid: "Gaszaehler Fallback Hotspot"
    password: "schmidt01"
  #manual_ip:
  # static_ip: 192.168.30.133
  # gateway: 192.168.30.1
  # subnet: 255.255.255.0
binary_sensor:
  - platform: gpio
    pin:
      number: GPIO22 # Beliebiger freier GPIO (z. B. GP22 = Pin 29)
```

```

    mode: INPUT_PULLUP
    inverted: true
    name: "Gaszähler Impuls"
    id: gas_pulse
    filters:
      - delayed_on: 100ms # Entprellung
    on_press:
      then:
        - lambda: |-
            id(total_pulses)++;
            ESP_LOGD("gas", "Impuls! Total: %d", id(total_pulses));
        - homeassistant.service:
            service: notify.mobile_app
            data:
              message: "Gaszähler: +{{ id(impuls_factor) }} m³"

sensor:
  - platform: uptime
    name: "RP2040 Uptime"
    unit_of_measurement: "s"
    icon: mdi:timer-outline
  - platform: internal_temperature
    name: "RP2040 CPU Temperatur"
    unit_of_measurement: "°C"
    device_class: temperature
    state_class: measurement
    icon: mdi:chip
# === SENSOR: Verbrauch in m³ ===
  - platform: template
    name: "Gasverbrauch m³"
    id: gas_m3
    device_class: gas
    state_class: total_increasing
    unit_of_measurement: "m³"
    accuracy_decimals: 3
    update_interval: 10s
    lambda: |-
      return id(initial_consumption) + (id(total_pulses) *
id(impuls_factor));
# === Optional: Energie in kWh (mit Brennwert) ===
  - platform: template
    name: "Gas Energie kWh"
    device_class: energy
    state_class: total_increasing
    unit_of_measurement: "kWh"
    accuracy_decimals: 2
    update_interval: 10s
    lambda: |-
      float brennwert = 11.2; // Aus Gasrechnung (kWh/m³)
      float zustandszahl = 0.95; // Aus Rechnung
      return (id(initial_consumption) + (id(total_pulses) *

```

Last update:

2025/11/11 04:33 haussteuerung:esphome:gaszaehler <https://drklipper.de/doku.php?id=haussteuerung:esphome:gaszaehler&rev=1762831980>

```
id(impuls_factor))) * brennwert * zustandszahl;
```

From:

<https://drklipper.de/> - **Dr. Klipper Wiki**

Permanent link:

<https://drklipper.de/doku.php?id=haussteuerung:esphome:gaszaehler&rev=1762831980>

Last update: **2025/11/11 04:33**

